

Fuels, Coolants, Lubricants etc. - Capacities

Vehicle components and their respective lubricants must match. Therefore use only brands tested and recommended by us. Please refer to the Factory Approved Service Products pamphlet, or inquire at your authorized Mercedes-Benz dealer.

| | Capacity | Fuels, coolants, lubricants etc. |
|-----------------------------|--|--|
| Engine with oil filter | 7.9 US qt (7.5 l) | Recommended engine oils |
| Automatic transmission | Initial fill: 7.7 US qt (7.3 l) Fluid change: 6.6 US qt (6.2 l) | Automatic transmission fluid |
| Rear axle | 1.4 US qt (1.3 l) | Hypoid gear oil SAE 90, 85 W 90 |
| Level control | approx. 2.1 US qt (2.0 l) | MB Hydraulic fluid |
| Power steering | approx. 1.1 US qt (1.0 l) | MB Power steering fluid |
| Accelerator control linkage | | Hydraulic fluid |
| Front wheel hubs | approx. 2.1 oz (60 g) each | High temperature roller bearing grease |
| Brake reservoir | approx. 0.5 US qt (0.5 l) | MB Brake fluid (DOT4) |

| | Capacity | Fuels, coolants, lubricants etc. |
|--|---|--|
| Windshield washer and headlamp cleaning system | approx. 5.3 US qt (5.0 l) | MB Windshield washer concentrate "S" ¹ |
| Rear window washer system | approx. 2.6 US qt (2.5 l) | |
| Fuel tank including a reserve of | approx. 19.0 US gal (72 l) approx. 2.6 US gal (10 l) | Premium unleaded gasoline: Posted Octane 91 (Average of 96 RON/86 MON) |
| Cooling system | approx. 10.0 US qt (9.5 l) | MB Anticorrosion/antifreeze |
| Air conditioner system | | R-134a refrigerant and special lubricant (Never R-12) |

- ¹ Use MB Windshield Washer Concentrate "S" and water for temperatures above freezing or MB Windshield Washer Concentrate "S" and commercially available premixed windshield washer solvent/antifreeze for temperatures below freezing. Follow suggested mixing ratios, see *Windshield/Headlamp Washer System* in Index.