

Model 126 (up to 08/85)

Model		Wheel Designation	Summer tires tubeless Designation	Winter tires tubeless Designation
126.032	126.033	Light alloy ¹⁾	205/70 R 14	205/70 R 14
126.037	126.043	6 1/2 J x 14 H2 ET 30	93 H	93 Q M + S
126.044				205/70 R 14
126.120	1985 ²⁾			93 T M + S
126.120	1983 1984	Light alloy ¹⁾ 6 J x 14 H2 ET 30	195/70 R 14 90 S	195/70 R 14 90 Q M + S 195/70 R 14 90 T M + S

¹⁾ Basic version steel wheels with the prescribed designation can be used for subsequent mounting of winter tires.

²⁾ Optionally equipped with wheels 6 J x 14 H2 ET 30.

40-0100 Survey wheels and tires

Subsequent conversion

Country-specific rules and regulations must be observed before considering conversion!

Series 70 tires

Model	Wheel Designation	Summer tires tubeless Designation	Winter tires tubeless Designation
126.021	Steel 6 1/2 J x 14 H2 ET 30	205/70 R 14 93 H	205/70 R 14 93 Q M + S ¹⁾
126.022 126.023	Light alloy 6 1/2 J x 14 H2 ET 30	205/70 VR 14	205/70 R 14 93 T M + S

Series 65 tires

Model	Wheel Designation	Summer tires tubeless Designation	Winter tires tubeless Designation
126.021	Steel 7 J x 15 H2 ET 25	205/65 R 15 93 H and 94 H	205/65 R 15 93 Q and 94 Q M + S ¹⁾
126.022 126.023 126.032 126.033 126.036 ²⁾ 126.037 ²⁾ 126.043 126.044 ²⁾	Light alloy ³⁾ 7 J x 15 H2 ET 25	205/65 R 15 94 V 205/65 VR 15	205/65 R 15 93 T/65 R 15 93 T and 94 T M + S

¹⁾ Only "T"-version tires (speed symbol "T") recommended.

²⁾ 15" wheels standard as of 09/85.

³⁾ Use wheels part no. 126 400 30 02 (flush wheel disk) for conversion.

Model 126 (as of 09/85)

Model	Wheel Designation	Summer tires tubeless Designation	Winter tires tubeless Designation
126.024 126.025 1988 1989 1990 1991	Light alloy ³⁾ 6 1/2 J x 15 H2 ET 21,5	205/65 R 15 94 H	205/65 R 15 93 Q and 94 Q M + S ²⁾ 205/65 R 15 93 T and 94 T M + S 205/65 R 15 94 H m + S
126.035 1988 1989 1990 1991		205/65 R 15 94 V 205/65 VR 15	
126.039 126.045 1986 1987	Light alloy ³⁾ 7 J x 15 H2 ET 25	205/65 R 15 94 V 205/65 VR 15	
126.039 126.045 1988 ¹⁾ 1989 1990 1991	Light alloy ³⁾ 6 1/2 J x 15 H2 ET 21,5		
126.125 1986 1987	Light alloy ³⁾ 7 J x 15 H2 ET 25	205/65 R 15 93 H and 94 H	
126.134 126.135 1990 1991	Light alloy ³⁾ 6 1/2 J x 15 H2 ET 21,5	205/65 R 15 94 H	

¹⁾ Conversion of light alloy wheels from 7 J x 15 H2 ET 25 to 6 1/2 J x 15 H2 ET 21.5 was phased into model year 1988.

²⁾ "Q"-version tires (speed symbol "Q") not recommended.

³⁾ Steel wheels part no. 124 400 28 02 can be used for subsequent mounting of winter tires. However, this requires wheel bolts for steel wheels, part no. 201 401 02 70 (bolt shank = 21 mm long), rubber valves, part no. 000 400 04 13 (53.5 mm long) and wheel trim covers.

40-0100 Survey wheels and tires

Subsequent conversions

None.