

14–150 Wiring diagrams

Model year 1975


Drawn with ignition switched off and below 17 °C oil temperature.

Connection of test instruments is drawn in dashed lines.

Color code


bl = blue	gn = green	vi = purple	a Switch air conditioning system/starter
br = brown	rt = red	ws = white	b Fuse no. 4 (15/54)
ge = yellow	sw = black		c Fuse no. 10 (15/54)
			d Fuse no. 2 (30)

Ignition switchover model 116.032/033



- | | | |
|--------------------------------------|--|--|
| 3 Temperature switch 62 °C | 24 Relay supplementary fan | 55 Switchover valve ignition advance/EGR (red) |
| 7 Temperature switch 17 °C | 25 Relay for disconnecting temperature switch 62 °C from temperature switch 100 °C | 57 Temperature switch 40 °C |
| 8 Temperature switch 100 °C | 27 Supplementary fan | 58 Relay EGR |
| 9 Switchover valve ignition (yellow) | 33 Switchover valve air injection (blue) | |
| 19 Relay switchover valve ignition | | |

EGR, air injection model 116.032/033



- | | | |
|--------------------------------------|--|--|
| 3 Temperature switch 62 °C | 24 Relay supplementary fan | 55 Switchover valve ignition advance/EGR (red) |
| 7 Temperature switch 17 °C | 25 Relay for disconnecting temperature switch 62 °C from temperature switch 100 °C | 57 Temperature switch 40 °C |
| 8 Temperature switch 100 °C | 27 Supplementary fan | 58 Relay EGR |
| 9 Switchover valve ignition (yellow) | 33 Switchover valve air injection (blue) | |
| 19 Relay switchover valve ignition | | |

Drawn with ignition switched off and below 17 °C oil temperature.


Connection of test instruments is drawn in dashed lines.

Color code

bl = blue gn = green sw = black
br = brown rs = pink ws = white
ge = yellow rt = red

a Temperature regulator air conditioning system
b Coupling electronic harness
c Fuse no. 12 (15/54)
d Fuse no. 8 (15/54)

Type 107.024/044



- | | | |
|--------------------------------------|--|--|
| 3 Temperature switch 62 °C | 24 Relay supplementary fan | 55 Switchover valve ignition advance/EGR (red) |
| 7 Temperature switch 17 °C | 25 Relay for disconnecting temperature switch 62 °C from temperature switch 100 °C | 57 Temperature switch 40 °C |
| 8 Temperature switch 100 °C | 27 Supplementary fan | 58 Relay EGR |
| 9 Switchover valve ignition (yellow) | 33 Switchover valve air injection (blue) | |
| 19 Relay switchover valve ignition | | |