



MAINTENANCE SYSTEM SHEET
Passenger Cars (USA) M.Y.'s 1986 – 1997
Including MY 98 SLK w/o "flexible" maintenance



Dealer Name:	Dealer Code:	Customer Name:
Technician:	R.O. Number:	Year & Model:
		Mileage:

107 124 126 129 140 170 201 202 210

Shaded areas indicate additional work to be performed together with respective Maintenance Service.

INSPECTION SERVICE

All Models → M.Y. 1991: Once at 800 – 1,000 miles/1,300 – 1,600 km.

All Models M.Y. 1992 → 1995: Once at 800 – 3,000 miles/1,300 – 4,800 km.

All Models M.Y. 1996: → Inspection service not required.

	If job no. required ANY additional service please note on R.O. and check ☒	Maintenance Job No.
Wheels and tires		
☐ Check, correct tire pressure	☐	4060
☐ Retighten wheel bolts. <i>Observe tightening torque!</i>	☐	4070
Underside of car		
☐ Adjust engine stop, rear engine mount (4MATIC only)	☐	2291
☐ Manual transmission oil change	☐	2601
☐ Transfer case fluid change (4MATIC only)	☐	2801
☐ Rear axle oil change	☐	3501
<i>Observe tightening torque!</i>		
☐ Retighten steering gear bolts (except model 140)	☐	4671
☐ Retighten exhaust flange	☐	4970
☐ Retighten exhaust system connections	☐	4971
Engine compartment		
☐ Engine oil and filter change	☐	0101
☐ Check condition and tension of V-belts 1) (engines 116 and 117)	☐	1350
<i>Check and correct fluid level:</i>		
☐ Engine coolant	☐	2011
☐ Automatic transmission fluid (→ M.Y. 1993)	☐	2710
☐ Level control, ADS, ASD, 4MATIC fluid	☐	3211
☐ Brake fluid	☐	4210
☐ Power steering fluid	☐	4611
☐ Battery electrolyte (→ M.Y. 1990)	☐	5410
☐ Windshield washer fluid	☐	8210
Trunk		
☐ Check, correct tire pressure (spare)	☐	4060
☐ Check and correct rear window washer fluid level (models 124.090/092/193/290)	☐	8210
☐ Check and correct hydraulic soft top fluid level (models 124.066, 129)	☐	7710

LUBRICATION SERVICE

All Diesel models except 140.134, 124.131, 210.020: Every 5,000 miles/8,000 km, or at least once a year.
All other models incl. 140.134, 124.131, 210.020: Every 7,500 miles/12,000 km, or at least once a year.

For Severe Operating Conditions, please refer to the respective Maintenance Booklet.

	If job no. required ANY additional service please note on R.O. and check ☒	Maintenance Job No.
Engine compartment		
☐ Engine oil and filter change	☐	0101
☐ Reset Maintenance Service Reminder		
☐ Inspect, lubricate throttle linkage (→ M.Y. 1995)	☐	3022
☐ Check and correct battery electrolyte level (→ M.Y. 1990)	☐	5410
☐ Lubricate hood hinges	☐	8821
☐ Reset Maintenance Service Reminder (model 170.447)	☐	
Underside of car		
☐ Adjust engine stop, rear engine mount (4MATIC only) Once at 7,500 miles/12,000 km	☐	2291

MAINTENANCE SERVICE

All models: Every 15,000 miles/24,000 km or every 2 years.

	If job no. required ANY additional service please note on R.O. and check ☒	Maintenance Job No.
☐ Brake test, parking brake check	☐	4290
4MATIC vehicles, observe  WARNING! in Maintenance Manual		
Interior		
☐ Check warning and indicator lamps, horn	☐	5451
☐ Clean cassette deck tape head	☐	8230
☐ Inspect headlamps and exterior lamps (incl. Daytime Running Lamps (CDN))	☐	8251
☐ Inspect/test windshield, rear window and headlamp wiper/washer system	☐	8252
☐ Heating and ventilation: Replace dust filter (models 202, 210)	☐	8381
☐ Inspect seat belts for damage	☐	9150
☐ Backrest lock, check operation (models 124.05/06, 140.070/076)	☐	9151

Every 45,000 miles/72,000 km (→ M.Y. 1993)

Every 45,000 miles/72,000 km or 2 years (M.Y. 1994 →)

☐ Replace air recirculation filter (model 140)	8383
☐ Replace activated charcoal filters (model 210)	8382

Body

☐ Lubricate door hinges (models 107, 126)	☐	7220
☐ Lubricate door locks (models 107, 126)	☐	7221
☐ Soft top locking lugs, check for wear (model 129)	☐	7750
☐ Clean antenna mast with special cleaning cloth	☐	8231
☐ Check condition of headlamp wiper blades	☐	8252
☐ Replace windshield wiper insert(s)	☐	8280

Every Two Years

☐ Clean water drains (→ M.Y. 1993)	☐	6030
☐ Clean and lubricate sliding roof rails (→ M.Y. 1993)	☐	7730
☐ Inspect body for paint damage	☐	9850

Every Three Years

☐ Clean and lubricate sliding roof rails (M.Y. '94 →, except model 210)	☐	7730
--	--------------------------	------

If job no. required ANY additional service
please note on R.O. and check ☒

Maintenance
Job No.

Wheels, tires & brakes

☐	Inspect, rotate wheels (please note specific instructions in Maint. Manual regarding models 140.070/076 M.Y. 95, 129.063/067/076 with AMG Sport Package, 170.447, 202.028 [C36 AMG])	☐	4050
☐	Inspect tires and record tread depth	☐	4051
☐	Correct tire pressure	☐	4060
☐	Check brake pad/disk thickness, check condition of discs	☐	4251
☐	Adjust parking brake (except models 140, 202, 210) Once at 15,000 miles/24,000 km (model 129)	☐	4261

Every Two Years

☐	Replace brake fluid	☐	4280
--------------------------	---------------------	--------------------------	------

Underside of car

☐	Inspect condition, routing, leaks, of components, lines and hoses	☐	0053
	<i>Check and correct fluid level:</i>		
☐	Manual transmission fluid	☐	2610
☐	Transfer case fluid (4MATIC only)	☐	2810
☐	Front axle fluid (4MATIC only)	☐	3310
☐	Rear axle oil (→ M.Y. 1993)	☐	3510
☐	Check front axle ball joints	☐	3353
☐	Check steering play	☐	4650
☐	Retighten steering gear bolts (→ M.Y. 1991)	☐	4671

Every Two Years

☐	Inspect suspension and body structure	☐	0090
--------------------------	---------------------------------------	--------------------------	------

Every 30,000 miles/48,000 km

☐	Check clutch disc for wear	☐	2551
☐	Automatic transmission fluid and filter change (except [M.Y. 1996] models 140.043/051/057/070/076, 129.067/076, [M.Y. 1997 → ALL])	☐	2702
☐	Inspect drive shaft flex discs	☐	4152
☐	Inspect parking brake cables (except models 140, 202, 210)	☐	4256
☐	Retighten steering gear bolts (M.Y. 1992 →) (except models 140, 210) <i>Observe tightening torque!</i>	☐	4671

Every 60,000 miles/96,000 km

☐	Replace fuel filter (except engines 102, 104, 119, 120 2))	☐	0780
☐	Check front axle ball joint freeplay (Models 124, 129, 201)	☐	3355

Engine compartment

☐	Inspect condition, routing, leaks, of components, lines and hoses	☐	0053
☐	Engine oil and filter change Reset Maintenance Service Reminder	☐	0101
☐	Check valve clearance (engine 102.983)	☐	0561
☐	Check injection timing (engines 602 and 603) Once at 15,000 miles/24,000 km (M.Y. 1990 → 1994)	☐	0760
☐	Check condition and tension of V-belts 1) (engines 116 and 117)	☐	1350
☐	Inspect poly-V-belt 1)	☐	1351
☐	Check spark plugs, replace if necessary 1)	☐	1550
☐	Replace spark plugs. Federal version (→ M.Y. 1987)		
	<i>Check and correct fluid level</i>		
☐	Engine coolant/antifreeze protection	☐	2010
☐	Automatic transmission fluid (→ M.Y. 1993)	☐	2710
☐	Level control, ADS, ASD, 4MATIC fluid	☐	3211
☐	Brake system	☐	4210

If job no. required ANY additional service
please note on R.O. and check ☒

Maintenance
Job No.

Engine compartment (continued)

Check and correct fluid level (continued)

☐	Power steering fluid	☐	4611
☐	Battery electrolyte (except models 124.034/036, 129, 140, 202, 210)	☐	5410
☐	Windshield washer fluid	☐	8210
☐	Inspect, lubricate engine throttle linkage	☐	3022
☐	Check A/C refrigerant charge (except model 210)	☐	8312
☐	Replace ventilation system dust filter (models 124, 129, 140 without activated charcoal filter)	☐	8381

Every 30,000 miles/48,000 km

☐	Check injection timing (Diesel engines) Once at 30,000 miles/48,000 km (M.Y. 1995 →)	☐	0760
☐	Replace fuel filter (Diesel engines only) (→ M.Y. 1996)	☐	0780
☐	Replace fuel prefilter (Diesel engines only) (→ M.Y. 1995)	☐	0781
☐	Replace air cleaner element (all engines → M.Y. 1996)	☐	0980
☐	Check condition and tension of V-belts ¹⁾ (→ M.Y. 1991) (engines 116 and 117)	☐	1350
☐	Inspect poly-V-belt (→ M.Y. 1991)	☐	1351
☐	Replace spark plugs	☐	1580

Every 45,000 miles/72,000 km (→ M.Y. 1993)

Every 45,000 miles/72,000 km or 2 years (M.Y. 1994 →)

☐	Replace dust filter (model 140, with activated charcoal filter only)	☐	8381
--------------------------	--	--------------------------	------

Every 60,000 miles/96,000 km

☐	Replace oxygen sensor. Once at 60,000 miles/96,000 km (model 201.028 California version only)	☐	1480
☐	Replace fuel filter (Diesel engine only) (M.Y. 1996 →)	☐	0780
☐	Replace fuel prefilter (Diesel engine only) (M.Y. 1996 →)	☐	0781
☐	Replace air cleaner element (M.Y. 1996 →)	☐	0980

Every 75,000 miles/120,000 km (→ M.Y. 1993)

Every 75,000 miles/120,000 km or 4 years (M.Y. 1994 →)

☐	Replace activated charcoal filter (model 140)	☐	8382
--------------------------	---	--------------------------	------

Every Three years

☐	Replace coolant (water/anticorrosion/antifreeze mixture)	☐	2080
☐	Battery electrolyte level (except maintenance-free batteries)	☐	5410

Trunk

☐	Correct tire pressure (spare)	☐	4060
Check and correct fluid level:			
☐	Rear window washer fluid (models 124.090/092/193/290)	☐	8210
☐	Hydraulic soft top fluid (models 124.066, 129)	☐	7710

¹⁾ Mercedes-Benz urges that this procedure be performed to maintain peak performance, although it is not required to maintain your emission warranty and will not affect Mercedes-Benz's recall liability.

²⁾ Replacement is not required at 60,000 miles on California version vehicles ¹⁾.