

	Capacity	Fuels, coolants, lubricants, etc.
Automatic transmission	Initial fill: 8.6 l (9.1 US qt) Fluid change: 7.7 l (8.1 US qt)	MB Automatic transmission fluid
Rear axle 420 SEL	1.3 l (1.4 US qt)	Hypoid gear oil SAE 90, 85 W 90
Rear axle 560 SEL, 560 SEC	1.3 l (1.4 US qt)	Hypoid gear oil SAE 90 for limited slip control
Power steering	1.3 l (1.4 US qt)	MB Power steering fluid
Level control	2.0 l (2.1 US qt)	Hydraulic fluid
Front wheel hubs	approx. 60 g (2.1 oz) each	High temperature roller bearing grease
Accelerator control linkage		Hydraulic fluid
Grease nipples		Multipurpose or lubrication grease
Door locks		Powered graphite
Brake reservoir	approx. 0.5 l (0.5 US qt)	MB Brake fluid (DOT4)

	Capacity	Fuels, coolants, lubricants, etc.
Windshield washer system and headlamp cleaning system	approx. 5.0 l (5.3 US qt)	MB Windshield washer concentrate "S" ¹
Fuel tank including a reserve of	approx. 90 l (23.8 US gal) approx. 12.5 l (3.3 US gal)	Premium unleaded gasoline: Posted Octane 91 (Average of 96 RON/86 MON)
Cooling system	approx. 13.0 l (13.7 US qt)	MB Anticorrosion/antifreeze

¹ Use MB Windshield Washer Concentrate "S" and water for temperatures above freezing or MB Windshield Washer Concentrate "S" and commercially available premixed windshield washer solvent/antifreeze for temperatures below freezing. Follow suggested mixing ratios, see page 51.